



7425 CHAVENELLE ROAD, DUBUQUE, IOWA 52002 PHONE: 563-690-1214

ATV RAMP

Model/UPC: 909213
909279

44" Wide ATV Ramp
48" Wide ATV Ramp

Maximum Weight Limit: 1000 pounds

WARNING: Be careful of pinch points at ramp folding and hinge locations.

YOUR RESPONSIBILITIES

It is your responsibility to carefully read and understand all instructions and safety warnings/labels, expiration date, and how to use the XOP, Inc. ATV Ramp and all additional XOP, Inc. merchandise before use. This owners manual and product labels provide important use and safety information. DO NOT Remove or Obscure any safety warning labels on any of your XOP products. Failure to read and follow these safety warnings could result in serious bodily injury or death. Please retain this manual and preserve all product labels for future reference.

CONTACT INFORMATION

Do not use XOP, Inc. merchandise until you read and thoroughly understand all instructions and safety warnings. You must read and follow all instructions and safety warnings before each use. Failure to read and follow these instructions and safety warnings could result in serious injury or death. If you are unsure of any instruction or safety warning, stop and contact XOP, Inc. immediately at 563-690-1214.

▼▼▼▼▼ SAFETY WARNINGS ▼▼▼▼▼

IMPORTANT PRODUCT INFORMATION

- Before each use inspect equipment carefully making sure all the parts are in working order and are in good condition. Do not use if any signs exist of product abrasion, damage, wear or defects. Replace any parts only with XOP, Inc. parts. Contact XOP, Inc. at 563-690-1214 with any product concerns or replacement part requests.
- Replace any parts only with XOP, Inc. parts. Use of any other parts will be considered a modification to the product and will void XOP, Inc. of any liability. Contact XOP, Inc. at 563-690-1214 with any product concerns or replacement part requests.
- There is an inherent risk involved in the use of ATV's and the loading, unloading, and hauling of these vehicles using any loading system. XOP, Inc. assumes no liability whatsoever for damage or injury incurred during the use of this product. A helmet should always be worn during loading and unloading an ATV.
- Lubricate hinges annually or as needed.
- Instructions should be kept in a safe place and reviewed at least annually. It is the responsibility of the ATV Ramp owner to furnish the Instructions to any person that borrows or purchases the XOP, Inc. equipment.
- Between usages store in dry place away from weather and sharp or abrasive objects.

▼▼▼▼▼ **ADDITIONAL SAFETY WARNINGS** ▼▼▼▼▼

ALWAYS:

- Use good judgment and practice general ATV safety measures and precautions.
- Inspect the equipment carefully making sure all the parts are in working order and are in good condition. Do not use if any signs exist of product abrasion, damage, or defects.
- Clean ramp of mud, snow, debris before ATV climbs or descends ramp. Excessive mud, snow and debris may cause slippage and cause loss of traction.
- Be careful of pinch points at ramp folding and hinge locations.
- Use only for intended purpose.
- Inspect the shipping carton for damage or evidence that it may have been opened before you received it.
- Only allow experienced ATV users to operate ATV when loading and unloading.
- Wear a helmet when operating ATV.

NEVER:

- Use any ATV ramp if you have not followed the manufacturer's care and maintenance guidelines.
- Exceed the recommended weight limit or safe working load of each XOP, Inc. product.
- Use an ATV or an ATV ramp if you are fatigued, on medication, physically impaired in any way, or have recently consumed alcohol or any other judgment altering drugs.
- Accelerate in order to ascend/descend ramp.
- Jump, bounce, or stomp on ramp.
- Make any modifications to this product. Any modifications void XOP, Inc. of any liability.

LOADING

- 1) Set the towing vehicle transmission in park and set the parking brake. If you are using a trailer be sure it is properly hitched or connected to the vehicle and is level.
- 2) On level ground, open ramp completely and rest rubber coated tailgate tabs on tailgate/trailer. Be careful of pinch points at ramp folding and hinge locations. Make sure:
 - ✓ Ramp is centered on tailgate/trailer.
 - ✓ Ramp is resting on hard-level ground.
 - ✓ Ramp is positioned on the tailgate/trailer bed at the lowest possible angle.
- 3) Keep the ramp at the lowest angle possible. This will help the ATV stay on all its wheels and not flip backwards during loading. Tailgate must never be higher than 1/2 the length of ramp or 33 inches from the ground.
- 4) Wrap safety chains around the tailgate support bars/cables and hook it back to itself, so the chain is taut and holds the ramp tightly against tailgate. Safety chains must be securely hooked up to vehicle to prevent ramp from sliding off tailgate.
- 5) Remove heavy or awkward gear from the ATV luggage rack before using the ramp. Ramp weight limit is 1000 lbs.
- 6) Confirm the towing vehicle transmission is in park and the parking brake is set. If you are using a trailer be sure it is properly hitched or connected to the vehicle and is level.

- 7) Always have a second adult person present to guide and spot ATV rider up the ramp. Stay a safe distance away from ramp and vehicle when spotting. Never allow a novice or a child to guide or load an ATV, and never stand in the rolling path of the ATV.
- 8) Wearing a helmet, set the ATV in the lowest/slowest gear available. Slowly but steadily creep up ramp with driver leaning forward to maintain balance.
- 9) Once vehicle is in truck bed/trailer, be sure to set ATV brake and securely tie down vehicle. Secure the ATV in truck bed or on trailer according to the Department of Transportation regulations and state laws.
- 10) Unhook safety chains and remove ramp from tailgate, fold, and store.

UNLOADING

- 1) Repeat Loading Steps 1-7.
- 2) Wearing a helmet, set ATV in low/reverse gear. Slowly back up until ATV is centered on ramp with driver leaning forward to maintain balance. Do not use throttle, only brakes until the tires of the ATV are on ground. Only then slowly throttle the ATV entirely off the ramp if necessary.
- 3) Unhook safety chains and remove ramp from tailgate, fold, and store.